



TW
F0208X

High density
oxidized polyolefin
wax powder

Product Introduction

High density oxidized polyolefin wax powder

Chemical composition

High density oxidized polyolefin

Technical data

| | |
|------------------------------|-------------------|
| Melting point (°C): | 138 |
| Acid value (mgKOH/g): | 25-30 |
| Average particle size (D50): | 20-21 |
| Average particle size (D90): | 32-36 |
| Specific gravity: | 0.99 |
| Appearance: | Fine white powder |

Features and advantages

1. Suitable for water-based coatings and inks;
2. Excellent wear resistance and transparency;
3. Excellent heat sealing strength or thermal adhesion, without affecting recoating properties;
4. Good scratch resistance, high glossiness, and good dispersibility;
5. Excellent hand feel and low surface smoothness.

Processing guidance

1. Add in the post production stage;
2. Mix and disperse at medium to high speed;
3. Due to its high melting point, it is recommended to grind and disperse.

Recommended use

1. This product is suitable for various water-based coatings, plastics, inks, and cosmetics fields;
2. Especially suitable for application scenarios such as water-based printed iron, rolled steel, woodwork, and industrial paint.

Storage and transportation

1. It should be cool, dry, and ventilated, below 60 °C, and should not be close to the flame;
2. The shelf life in the sealed original packaging is two years.

Recommended dosage

0.3-5% of the total weight.

Packing

Packed in 20 kilograms of paper bags.

We provide these data and technical advice with our existing knowledge. However, because of the different application environment, please users according to the test application, we can not guarantee all the circumstances.

JIANGSU TIANWEN NEW MATERIAL TECHNOLOGY CO.,LTD.
Xinbei District Changzhou Jiangsu
Tel:0519-81884271 Fax:0519-85788271