



### **Product introduction**

Sand flour

### **Chemical composition**

Modified polymer sand wax

### **Features and advantages**

1. It can withstand the high temperature of 220°C;
2. The hand feels smooth and does not prick the hand;
3. Good compatibility with various systems;
4. Both decorative and scratch and wear resistance.

### **Recommended use**

1. This product is suitable for all kinds of industrial paint, wood paint coil steel and ink systems.

### **Recommended dosage**

3-8% of the total weight, adjusted according to the sand grain effect and film thickness.

### **Technical data**

|                              |                   |
|------------------------------|-------------------|
| Melting point (°C):          | >160              |
| Average particle size (D50): | 30 ± 2            |
| Average particle size (D90): | 45 ± 3            |
| Proportion:                  | 0.9               |
| Exterior:                    | Fine white powder |

### **Processing guidance**

1. Add in the later stage of production;
2. Stir and disperse at medium and high speed;
3. In order to ensure uniform particle size, grinding should be avoided.

### **Storage and transportation**

1. Cool, dry and ventilated, below 60°C, not close to kindling;
2. The shelf life in the sealed container is two years.

### **Package**

20kg paper bag.

We provide these data and technical advice with our existing knowledge. However, because of the different application environment, please users according to the test application, we can not guarantee all the circumstances.

JIANGSU TIANWEN NEW MATERIAL TECHNOLOGY CO.,LTD.  
Xinbei District Changzhou Jiangsu  
Tel:0519-81884271 Fax:0519-85788271