



Product Introduction

Spherical polyamide ultrafine wax powder

Chemical composition

Polyamide 612

Feature benefits

1. High porosity and good dispersibility;
2. The melting point is high, and it can withstand 350°C;
3. The extremely narrow particle size distribution makes the product performance stable;
4. Extremely high sphericity can significantly improve the surface touch and scratch resistance of the paint film.

Recommended use

1. Various plastics and coatings;
2. Various coatings, especially powder coatings and solvent based, water-based, UV curable wood coatings;
3. Ink.

Recommended dosage

0.5-5% of total weight.

Technical data

Melting point (°C):	200
Average particle size (D50):	40±3
Average particle size (D90):	60±5
Specific gravity:	1.06
Appearance:	Fine white powder

Processing guidance

1. Add in the post production stage;
2. Mix and disperse at medium to high speed;
3. Because the product is spherical, grinding should be stopped to avoid damaging the sphericity.

Storage and transportation

1. It is cool, dry, and ventilated, below 60 °C, and must not be near the kindling;
2. The shelf life in sealed containers is two years.

Packing

Packed in 20 kg paper bags.

We provide these data and technical advice with our existing knowledge. However, because of the different application environment, please users according to the test application, we can not guarantee all the circumstances.

JIANGSU TIANWEN NEW MATERIAL TECHNOLOGY CO.,LTD.
Xinbei District Changzhou Jiangsu
Tel:0519-81884271 Fax:0519-85788271