



**Product introduction**

Multi-purpose polyethylene wax

**Technical data**

Test items	Test results	Experimental method
Viscosity (CPS@140°C)	15±5	Brookfield Visco-meter
Density (g/cm <sup>3</sup> @23°C)	0.91-0.93	ASTM D1505
Softening Point (°C)	115±3	ASTM E28
Penetration (d-mm@25°C)	≤ 1	ASTM D5
Acid value (mg KOH/g)	—	ASTM D1386
Exterior	White granular powder	Visually

**Features and advantages**

1. Plastic and rubber
2. Adhesives (hot melt adhesives, etc.)
3. Lubricant, release agent
4. Inks, paints including powder coatings
5. Cable filler compound
6. Dispersion of pigments

**Storage and transportation**

1. Cool, dry and ventilated, below 60 °C, not close to fire;
2. Shelf life in sealed packaging is two years.

**Package**

Packed in 25kg paper bag.

We provide these data and technical advice with our existing knowledge. However, because of the different application environment, please users according to the test application, we can not guarantee all the circumstances.

JIANGSU TIANWEN NEW MATERIAL TECHNOLOGY CO.,LTD.  
 Xinbei District Changzhou Jiangsu  
 Tel:0519-81884271 Fax:0519-85788271